

Total Flat Fan-Coil Bi2 SL SMART		SL Smart 200	SL Smart 400	SL Smart 600	SL Smart 800	SL Smart 1000
ΨΥΞΗ θερμ. νερού in 7° out 12° C, θερμ. δωμ. 27° C	kW	0,83	1,76	2,56	3,3	3,81
Water Flow Rate	l/h	142	302	446	573	655
Water Pressure Loss	kPa	13,1	8,2	19	18,7	18,2
ΘΕΡΜΑΝΣΗ (50° C) θερμ. νερού in 50° C, θερμ. δωμ. 20° C	kW	0,98	2,15	2,89	3,82	4,35
Water Flow Rate (50° C)	l/h	84	185	249	329	374
Water Pressure Loss (50° C)	kPa	4,72	2,94	5,57	4,49	4,23
ΘΕΡΜΑΝΣΗ (70° C) θερμ. νερού in 70° out 60° C, θερμ. δωμ. 20° C	kW	1,77	3,88	5,21	6,88	7,83
Water Flow Rate (70° C)	l/h	152	334	448	592	673
Water Pressure Loss (70° C)	kPa	10,9	7	14,3	12,7	12,5
ΠΑΡΟΧΗ ΑΕΡΑ max-min	m³ /h	160-100	320-170	460-180	575-370	650-420
Sound Power max-min Lw	dB(A)	52-38	53-39	53-41	53-39	54-42
Sound Pressure	dB(A)	34	36	37	35	38
Είσοδος / Εξοδος νερού	inches	<i>Eurokonus 3/4</i>	<i>Eurokonus 3/4</i>	<i>Eurokonus 3/4</i>	<i>Eurokonus 3/4</i>	<i>Eurokonus 3/4</i>
Χωρητικότητα Στοιχείου	l	0,47	0,8	1,13	1,46	1,8
Απορροφούμενη Ισχύς max-min	W	17-6	28-9	35-9	38-17	43-19
Παροχή	V/ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
ΜΗΚΟΣ	mm	759	959	1159	1359	1559
ΥΨΟΣ (χωρίς πέλματα)	mm	579	579	579	579	579
ΠΑΧΟΣ ΑΝΩ/ΚΑΤΩ	mm	129/150	129/150	129/150	129/150	129/150
ΒΑΡΟΣ	kg	13,5	15,5	19,5	22,5	25,5
ΧΡΩΜΑ ΛΕΥΚΟ	Κωδικός	01409	01410	01411	01412	01413