

# CONSOLE



## STANDARD INVERTER (R410A)

CQ09  
CQ12  
CQ18



LG participates in the ECP programme for EUROVENT AC program.  
Check ongoing validity of certification  
: [www.eurovent-certification.com](http://www.eurovent-certification.com)

UU09W  
UU12W



UU18W



INDOOR				CQ09.NAO	CQ12.NAO	CQ18.NAO
Capacity	Cooling	Min / Nom / Max	kW	1.3 / 2.6 / 3.4	1.4 / 3.5 / 3.7	2.2 / 5.0 / 5.6
	Heating	Min / Nom / Max	kW	1.4 / 3.1 / 4.2	1.6 / 4.0 / 4.4	2.2 / 4.8 / 5.8
Low Temperature Capacity	Heating -7°C	Max	kW	3.4	3.6	4.9
Power Input (Set)	Cooling	Nom	kW	0.64	1.06	1.55
	Heating	Nom	kW	0.74	1.08	1.50
Power Input (Indoor)		Nom	W	20	30	40
Running Current	Cooling / Heating	Nom	A	3.42 / 3.87	5.02 / 5.03	7.0 / 6.9
Power Supply			Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
EER				3.98	3.30	3.23
COP				4.19	3.70	3.20
SEER				5.11	5.31	6.2
SCOP				3.81	3.81	3.81
Pdesign (@ -10°C)			kW	2.8	3.0	3.8
Seasonal Energy Label	Cooling / Heating (A++ to E Scale)			A / A	A / A	A++ / A
Annual Energy Consumption	Cooling / Heating		kWh	172 / 1,032	231 / 1,105	282 / 1,396
Piping Connection	Liquid		mm (inch)	Ø6.35 (1/4)	Ø6.35 (1/4)	Ø6.35 (1/4)
	Gas		mm (inch)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø12.7 (1/2)
	Drain	O.D. / I.D.	mm	21.5 / 16.0	21.5 / 16.0	21.5 / 16.0
Air Flow Rate		High / Medium / Low	m³/min	8.5 / 6.7 / 5.0	9.0 / 6.9 / 5.2	10.1 / 8.6 / 7.2
Sound Pressure	Cooling	High / Medium / Low	dBA	38 / 32 / 27	39 / 32 / 27	44 / 39 / 35
Sound Power	Cooling	Max	dBA	53	56	60
Dehumidification Rate			l/h	1.2	1.4	2.3
Dimensions	Body	W x H x D	mm	700 x 600 x 210	700 x 600 x 210	700 x 600 x 210
Net Weight	Body		kg	14.0	14.0	14.0

OUTDOOR				UU09W.ULO	UU12W.ULO	UU18W.UE4
Compressor	Type			Rotary	Rotary	Twin Rotary
Airflow Rate		Nom	m³/min	32	32	50
Sound Pressure	Cooling	Nom	dBA	47	47	47
	Heating	Nom	dBA	48	48	52
Sound Power	Cooling	Max	dBA	56	57	63
Dimensions	W x H x D		mm	770 x 540 x 245	770 x 540 x 245	870 x 655 x 320
Net Weight			kg	32.0	32.0	44.6
Refrigerant	Type		-	R410A	R410A	R410A
	Charge		g	1,000	1,000	1,300
	Additional Charge		g/m	20	20	20
	GWP		-	2,087.5	2,087.5	2,087.5
	TCO <sub>2</sub> eq		-	2.1	2.1	2.7
Operation Range (Outdoor)	Cooling	Min / Max	°C DB	-10 / 43	-10 / 43	-15 / 48
	Heating	Min / Max	°C WB	-18 / 18	-18 / 18	-18 / 18
Power Supply			Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable			No. x mm²	3C x 2.5	3C x 2.5	3C x 2.5
Transmission Cable			No. x mm²	4C x 0.75	4C x 0.75	4C x 0.75
Circuit Breaker			A	15	15	20
Piping Length Total		Min / Max	m	5 / 15	5 / 15	5 / 30
Piping Elevation Difference	IDU - ODU	Max	m	10	10	30
Piping Connection	Liquid		mm (inch)	Ø6.35 (1/4)	Ø6.35 (1/4)	Ø6.35 (1/4)
	Gas		mm (inch)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø12.7 (1/2)

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

Note : 1. Due to our policy of innovation some specifications may be changed without notification.

2. Definition of Power Input Nominal conditions – Performance tested under EN14511

3. Capacities are based on the following conditions : Cooling : - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB  
Heating : - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB

4. Annual energy consumption : based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition

5. This product contains fluorinated greenhouse gases (R410A)